

WAVEGUIDE BROADWALL COUPLERS

General Specifications

Mainline VSWR : 1.08:1
 Secondary Line : 1.20:1
 Directivity : 40 dB

MODEL NO.	FREQUENCY RANGE - GHz	COUPLING-dB	WG SIZE	FLANGE
1430-016-01	5.50-8.20	6+/-1.0	WR137	CMR137
1430-016-02	5.50-8.20	10+/-1.0	WR137	CMR137
1430-016-03	5.50-8.20	20+/-1.0	WR137	CMR137
1430-017-01	8.20-13.0	6+/-1.0	WR90	CMR90
1430-017-02	8.20-13.0	10+/-1.0	WR90	CMR90
1430-017-03	8.20-13.0	20+/-1.0	WR90	CMR90
1430-015-01	10.0-15.0	6+/-1.0	WR75	CMR75
1430-015-02	10.0-15.0	10+/-1.0	WR75	CMR75
1430-015-03	10.0-15.0	20+/-1.0	WR75	CMR75
1430-018-01	12.40-18.0	6+/-1.0	WR62	CMR62
1430-018-01	12.40-18.0	10+/-1.0	WR62	CMR62
1430-018-01	12.40-18.0	20+/-1.0	WR62	CMR62
1430-019-01	18.0-26.5	6+/-1.0	WR42	CMR42
1430-019-02	18.0-26.5	10+/-1.0	WR42	CMR42
1430-019-03	18.0-26.5	20+/-1.0	WR42	CMR42