

WAVEGUIDE TERMINATIONS

Precision Termination Specifications

MODEL NO.	FREQ. RANGE - GHz	VSWR	CW POWER -W	MATING FLANGE	MOUNTING SCREW	MATERIAL
A6534-01	2.60-3.95	1.01	10	CMR-284	8-32 6PL /.172 6PL	ALUM.
A6534-02				CPR-284F	0.259 10 PL	
A6534-03				CPR-284G		
A6534-04				UG-53/U	0.259 8 PL	
A6534-05				CMR-284	0.172 12 PL	
A6534-06				CMR-284	8-32 12 PL	
A6535-01	3.30-4.90	1.01	10	CMR-229	6-32 4PL 0.149 4PL	ALUM.
A6535-02				CPR-229F	0.259 10 PL	
A6535-03				CPR-229G		
A6535-04				CMR-229	0.149 8 PL	
A6535-05				CMR-229	6-32 8 PL	
A6536-01	3.95-5.85	1.01	8	CMR-187	6-32 4PL/.149 4PL	ALUM.
A6536-02				CPR-187F	0.259 10PL	
A6536-03				CPR-187G		
A6536-04				CMR-187	0.149 8PL	
A6536-05				CMR-187	6-32 8PL	
A6537-01	4.90-7.05	1.01	7	CPR-159G	0.259 8PL	ALUM.
A6537-02				CPR-159F		
A6537-03				CMR-159	6-32 4PL/.149 4PL	
A6537-04				CMR-159	6-32 8PL	
A6537-05				CMR-159	0.149 8PL	
A6538-01	5.85-8.20	1.01	6	CMR-137	6-32 4PL/.149 4PL	ALUM.
A6538-02				CPR-137F	0.198 8PL	
A6538-03				CPR-137G		
A6538-04				CMR-137	0.149 8PL	
A6538-05				CMR-137	6-32 8PL	
A6539-01	7.05-10.4	1.01	5	CMR-112	6-32 4PL/.149 4PL	ALUM.
A6539-02				CPR-112F	0.169 8PL	
A6539-03				CPR-112G		
A6539-04				CMR-112	0.149 8PL	
A6539-05				CMR-112	6-32 8PL	

Precision Termination Specifications

MODEL NO.	FREQ. RANGE - GHz	VSWR	CW POWER -W	MATING FLANGE	MOUNTING SCREW	MATERIAL
A6540-01	8.20-12.40	1.01	3	CMR-90	6-32 6PL / .149 6PL	ALUM.
A6540-02				CPR-90F	0.169 8 PL	
A6540-03				CPR-90G		
A6540-04				UG-39/U	0.169 4PL	
A6540-05				CMR-90	0.149 8 PL	
A6540-06				CMR-90	6-32 8 PL	
A6541-01	10.0-15.0	1.01	2	WR-75	0.147 4PL	ALUM.
A6541-02				WR75-CHOKE	6-32 4 PL	
A6541-03				CPR-75F	0.147 8 PL	
A6541-04				CPR-75G		
A6541-05				WR-75 O-RING GROOVE	0.147 4 PL	
A6544-01	18.0-26.5	1.01	1	UG-595/U	0.119 4PL	ALUM.
A6544-02				UG-596A/U	4-40 4 PL	
A6544-03				UG-596A/U	0.147 8PL	
A6544-04				UG-596/U	4-40 4PL	
A6545-01	26.0-40.0	1.01	1	UG-599/U	0.119 4PL	ALUM.